



## **Menke Linx Small Character C.I.J. System**

*Here are a few reasons why more companies are choosing Menke's Linx:*

**Reliability: The Linx System is the most advanced technology on the market today. The main reasons for this are:**

- The Linx system **does not require shop air** eliminating problems associated with air pressure, water and debris in air lines.
- The Linx Printhead is sealed protecting the electronics from solvents and the plant environment.
- The **Linx Printhead has no moving parts**. No wear parts means less downtime.
- The **Linx measures the viscosity of each droplet in the printhead** virtually eliminating leaking or clogging by making sure the ink does not get too thick or thin.

**Ease of Use/Maintenance : The Linx System is simpler for your operator to use and your maintenance staff to maintain than the competition.**

- **Simple user interface**
- **Auto-flush feature and less manual cleaning.** Do not need to clean the printhead manually more than once per week. The competition requires once or twice per day.
- **Filters last up to 2,000 hours.**
- **No need to change out nozzles or make adjustments to your printhead.**

**Menke's Service/Support : We take care of our customers better than anyone in the industry so you won't want to go anywhere else!**

**Family owned and operated since 1945. Experience the Menke difference:**

- **Local Warehouse with ink/solvent in-stock.**
- **Local Factory trained technician at rates you can afford after the sale!** Our service rates are typically 25% to 50% less than our competitors.
- **Free hazardous ink waste removal** for ink/solvent customers.
- **Free Maintenance for the 1<sup>st</sup> Year:** Includes four complimentary service visits.

**Contact us today for a free consultation and/or demo at:**

**Toll Free: (800)231-6023 • Fax #: (562)921-1380**

**[www.menkemarking.com](http://www.menkemarking.com) or [sales@menkemarking.com](mailto:sales@menkemarking.com)**

## LINX 4900

### The Best 2-Line Printer to Date



Designed especially for 2-line printing



IP55 Compliant for washdown and harsh environments



#### Cleaner

- Stainless steel cover has no dirt traps and provides a surface off which liquid naturally slides.
- IP55 rating for washdown environments such as food packaging.
- Autoflush of printer at shutdown ensures trouble free operation.
- Mistake-proof ink and solvent refilling.



#### Clearer

- Printhead designed especially for 2-line printing.
- All printhead parameters are maintained by the printer for trouble-free viscosity control and consistent print quality.
- Sealed printhead design. No manual adjustments required.



#### Smarter

- Clear, simple user interface means messages are created, selected, edited and printed right the first time.
- Up to 50 messages can be stored and selected for easy identification.
- One button shutdown with automatic printhead flush.



# MENKE

TEL 800-231-6023  
FAX 562-921-1184



## DIMENSIONS

CONTROLLER	22.75" L x 19.01" W x 9.44" H (578mm X 483mm X 240mm)
PRINTHEAD	8.5" L x 1.675" H (225mm x 42 mm)



## LINX 4900 SYSTEM FEATURES

### EASE OF USE

- **FULL SIZE QWERTY KEYBOARD.** The full size keyboard built into the printer, combined with the full character display, makes the Linx 4900 user friendly and easy to operate.
- **50 MESSAGE CAPABILITY.** Up to 50 messages can be programmed with minimal keystrokes. Sequential numbers, expiration dates, time & date codes are all available in the Linx 4900.
- **1 OR 2 LINE PRINTING.** Text in a variety of fonts with separate boldness are standard on the Linx 4900.
- **WYSIWYG (what you see is what you get).** True on screen representation of messages makes it very easy for operators to create messages.

### RELIABILITY

- **HERMETICALLY SEALED PRINT HEAD** has no adjustment points. This means reduced maintenance on the Linx 4900.
- **AUTOPURGE PRINT HEAD.** On shutdown the Linx 4900 will perform a flush cleaning of the print head and lines. This ensures a simple one-button startup.
- **T.O.F. (TIME OF FLIGHT).** The Linx 4900 actually measures the viscosity of the ink in the print head while it is being cycled. The time of flight measurement automatically adjusts pressure and/or solvent levels continuously. This auto-adjustment reduces operator intervention while maintaining optimum print quality.
- **IP55 RATED STAINLESS STEEL ENCLOSURE** on the Linx 4900 makes it very reliable in harsh environments.
- **NO EXTERNAL PLANT AIR REQUIRED.** Linx printers do not need plant air, (typically filtered to lab quality) for use. This makes the Linx 4900 portable. One printer can serve 2 or more production lines, as needed.
- **FAST DRY INKS.** The standard MEK black ink dries instantly on any surface. Other ink formulations are available.